

## MAX glass wind shield electronic balance

### Main features:

- Removable glass wind shield
- External calibration
- High readability load cell weighing system
- Large Green backlight LCD display
- 16 units:g,ct,oz,lb,dwt,ozt,tl,T,tl.H,tl.J,GN,dr,MM,tola,GSM,T/A/R,T/M/R
- Piece count mode
- Zero,Tare functions
- Auto OFF function
- Overload protection, Overload warning
- USB serial interface
- Optional extra display

### Technical data:

- Power supply:Lithium battery with 12V/1000mA adaptor
- Scale body size: 215x310x300mm
- Casing material:Plastic
- Pan material:Stainless steel
- LCD Display digits: 6digits
- Digit height: 15mm
- Working temp:0°C - 40°C, 32°F - 104°F



Model	Capacity (g)	Readability (g)	Repeatability (g)	Linearity (g)	Corner tolerance	Pan(mm)	Suggest warm-up time (mins)	Net weight	Shipping carton	Meas (mm)	Carton weight
MAX-120	120	0.001	±0.002	±0.002	±0.003	Ø98	20	3.8kg	2pcs/ctn	650x470x450	12.04kg
MAX-210	210	0.001	±0.002	±0.002	±0.003	Ø98	20	3.8kg	2pcs/ctn	650x470x450	12.04kg
MAX-310	310	0.001	±0.002	±0.002	±0.003	Ø98	20	3.8kg	2pcs/ctn	650x470x450	12.04kg
MAX-1200	1200	0.01	±0.02	±0.02	±0.03	Ø115	20	3.8kg	2pcs/ctn	650x470x450	12.04kg
MAX-2100	2100	0.01	±0.02	±0.02	±0.03	Ø115	20	3.8kg	2pcs/ctn	650x470x450	12.04kg
MAX-3100	3100	0.01	±0.01	±0.01	±0.02	Ø115	20	2.2kg	4pcs/ctn	580x420x390	12.9kg
MAX-3100	3100	0.1	±0.2	±0.2	±0.3	175x210	15	2.2kg	4pcs/ctn	580x420x390	12.9kg
MAX-6100	6100	0.1	±0.2	±0.2	±0.3	175x210	15	2.2kg	4pcs/ctn	580x420x390	12.9kg
MAX-10000	10000	0.1	±0.2	±0.2	±0.3	175x210	15	2.2kg	4pcs/ctn	580x420x390	12.9kg